



SILANOS
QUALITY MADE EASY



E40H Digit2

Glasswasher

FEATURES

Control panel
Cabinet
Wash impellers
Rinse impellers
Energy-saving 'stand-by' function
Drain pump
Detergent dosing
Rinse aid dosing
HY-NRG - Break tank with booster pump 0,18kW
A - Water softener built in

standard

digit2
Single skin panel
S/S
Polypropylene

•

optional

⊙

S/S
⊙
•
•
Peristaltic
⊙
•

TECHNICAL DATA

Voltage
Energy consumption
Inlet water
Wash pump
Boiler element
Wash tank element
Wash tank
Water consumption per cycle
Basket
Washing cycles
Racks in number
Noise
Weight

230V~ 50Hz
2,77
55 - 7/12 - 1,5/3
0,17
2,6
1,6
12
2,4
40x40
60/120/180/480
60/30/20/8
48
31

Volt
kW
°C - °F - bar
kW
kW
lt
lt
cm
sec
h
dBA
kg



E50 Digit3

Dishwasher

FEATURES

Control panel
Cabinet
Wash impellers
Rinse impellers
Energy-saving 'stand-by' function
Drain pump
Detergent dosing
Rinse aid dosing
HY-NRG - Break tank with booster pump 0,18kW
A - Water softener built in

standard

optional

digit3
Single skin panel
S/S
Polypropylene
S/S
•
•
Peristaltic
•
•

TECHNICAL DATA

Voltage
Energy consumption
Inlet water
Wash pump
Boiler element
Wash tank element
Wash tank
Water consumption per cycle
Basket
Washing cycles
Racks in number
Noise
Weight

3N PE 400V 50Hz
4,9
55 - 7/12 - 1,5/3
0,4
4,5
2
23
2,4
50x50
60/120/180/480
60/30/20/8
62
47
Volt
kW
°C - °F - bar
kW
kW
kW
lt
lt
cm
sec
h
dBA
kg





TC150 - TCA150

Rack conveyor

FEATURES

Control panel	Digital	
Double skinned cabinet	✓	
Inlet splashguard	TCS	TC
Break tank with booster pump 0,18kW	✓	
Rinse economiser	✓	
Autostart/autostop		•
External tank drain system without overflow	✓	
Drain pump		•
Insulated boiler	✓	
Detergent dosing		•
Rinse aid dosing		•
CRV - Heat recovery and steam condenser 0,12kW		•
AS - Dryer 6,55-9,55-12,55 kW with inlet splashguard		•
ASA - Dryer on courbe 6,55-9,55-12,55 kW with inlet splashguard		•
Corner prewash		•

TECHNICAL DATA

Voltage	3N PE 400V 50Hz	Volt
Energy consumption	24,5/30,5	kW
Water consumption	246	l/h
Racks/hour in number (speed 1/2/3)	99/149/200	rks/h
Motorgear	0,25	kW
Prewash pump	1,1	kW
Wash pump	2	kW
1st rinse pump	⊙	kW
break tank pump	0,18	kW
Prewash tank	55	lt
Wash tank	80	lt
1st rinse tank	⊙	lt
Boiler	12	lt
Wash tank element	9	kW
1st rinse element	⊙	kW
Boiler element	12/18	kW
Inlet water	55/7-12	°C/°f
Noise	72	dBA



SILANOS
QUALITY MADE EASY